

PoE Switches

Provision-ISR PoE Switches are designed to push power and data further and much stronger, ending the discouraging signal transmission loss. Our PoE series offer ultra-long distance transmission, reliable power supplies with high-voltage surge protection, and support multiple protocols, providing the installer with the highest flexibility in the design of the system and the wiring.



PoES-08120C+2I-V2

8 Downlink + 2 Uplink 10/100Mbps 120W PoE Switch with CCTV Mode

The "PoES-08120C+2I-V2" is a 10/100 8-port PoE + 2 downlink/uplink ports Ethernet switch. The switch auto-detects connected IEEE802.3af/at compliant Powered Devices (PD) and supplies power to them. The PoE objective is to deploy independent power to places with no power source and outlets. The CCTV mode allows a camera connection up to a 250m distance.



MAIN FEATURES

- PoES-08120C+2I-V2
- PoE Ports: 8
- Downlink Ports: 8
- Uplink Ports: 2
- Download Speed: 10/100Mbps
- Uplink Speed: 10/100Mbps
- Total Power: 120W
- Maximum Power Per Channel: 30W
- Backbone Bandwidth: 2Gbps
- Buffer Size: 448Kbit
- MAC Address Table: 1K
- CCTV Mode: Selectable Standard/CCTV Mode
- Power Supply: 100-240VAC
- Power Consumption: PoE on: 125W Max. / PoE off: 5W Max.
- Dimensions: 220*150*44mm
- Weight: ~1Kg



<https://provision-isr.com>

SPECIFICATIONS

Interface	
Downlink Ports	8*10/100Mbps RJ45 port
Uplink Ports	2 x 10/100Mbps port
SFP Ports	N/A
PoE	
PoE Ports	8
Ethernet Standards	IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3af, IEEE802.3at
PoE Total Power	120W
Average Power Per Channel	15.4W
Maximum Power Per Channel	30W
Data Processing	
Backbone Bandwidth	2Gbps
Buffer Size	448Kbit
MAC Address Table	1K
VLAN	N/A
Network Media	
EIA/TIA-568	100Ω STP (Maximum 100m)
10BASE-T	UTP Category 3, 4, 5 Cable (Maximum 100m)
100BASE-TX	UTP Category 5, 5e Cable (maximum 100m)
1000BASE-T	N/A
1000BASE-X	N/A
Special	
CCTV Mode	Selectable Standard/CCTV Mode
Surge Protector	Different mode±4KV common mode±2KV

Wall Bracket	No
Rack Bracket	No
K-Slot (Anti Theft)	No
Power	
Status Monitor	N/A
Keep Alive	N/A
Power Supply	100-240VAC
Others	
Power Consumption	PoE on: 125W Max. / PoE off: 5W Max.
Fan	No
Dimensions	220*150*44mm
Weight	~1Kg
Operating Temperature	0°C ~ 40 °C